



SOPHIE - WHITE OAK

With classic measures this herringbone pattern parquet is enriched with decorative small knots, slashes of lighter sapwood and distinctive medullary rays. Nano-ceramic fortified matt varnish is very resistant to scratches and wear. Strong HDF-mid-layer is very stable in changing humidity conditions and helps prevent dents from falling objects.

Products are available in 4 different colours - natural oak, white oak, smoke grey and dark brown.

Measures: 12 x 120 x 600 mm , 4 left hand and 4 right hand boards in one package

Floating or glued down installation

| | | | | | |
|--------------------------|---|---------------------------------|---------------|--|--------------------------------|
| PRODUCT | SOPHIE | Thickness (mm) | 12 | Fire resistance EN13501-1 | Dfl s1 |
| SKU | 0708031 | Wearlayer thickness (mm) | 3 | Formaldehyde Emission Class EN717-1 | E1 |
| EAN | 4820226620037 | Width (mm) | 120 | Thermal conductivity EN12667 | 0.12 ... 0.18 W / (mK) |
| Wood species | oak | Length (mm) | 600 | Biological life | Class 1 |
| Pattern | herringbone | m² in package | 0.576 | Floor heating | Suitable |
| Selection grade | natur | Weight kg/m² | 9.6 | Package | 4 left and 4 right hand boards |
| Surface treatment | matt varnish with nano-ceramic particles | Joint | Unifit X (5g) | | |
| Tone | light | Bevelled | 4 sides | Installation method | Floating or glue-down |
| Allowed: | color variation, medullary rays, full knots (diameter up to 35 mm), refurbished knots (diameter up to 20 mm), restored cracks (diameter up to 0,5 mm), sapwood (diameter up to 1/3 of plank area), wormholes (diameter up to 1 mm). | | | | |